

Constant-Temperature Incubator

Features:

- * Intelligent temperature controller, based on microprocessor with PID parameters controlling function, and LCD display make temperature accurate and reliable.
- * The double door makes the temperature fluctuation small. The toughened-glass inner door is convenient to observe chamber condition without affecting chamber temperature.
- * The working chamber adopts 304 stainless steel and round angle structure, easy to clean.



BJPX-H30



BJPX-H50/80/160/270

Optional Accessories: * Independent temperature protector.

Technical Parameters:

Model	BJPX-H30	BJPX-H50	BJPX-H80	BJPX-H160	BJPX-H270
Capacity	30L	50L	80L	160L	270L
Temp. Range	RT+5~65°C				
Temp. Fluctuation	±0.3°C				
Time Setting	1~9999mins				
Alarm	Over-temperature alarm;audible and visual alarm.				
Shelves	2 pcs/adjustable			3 pcs/adjustable	
Consumption	200W	210W	280W	380W	570W
Power Supply	AC110/220V±10%, 50/60Hz				
Internal Size(mm)	320*300*315	350*350*410	400*400*500	500*500*650	600*600*750
External Size(mm)	650*470*510	510*520*800	580*570*890	680*670*1050	770*780*1150
Package Size(mm)	780*600*680	600*610*850	670*650*940	800*790*1200	890*890*1300
Gross Weight(kg)	45	55	57	90	130